



CLEAN OIL
BRIGHT IDEAS

B 27/27

CJC™ Offline Filter Insert

CJC™ Product Sheet

APPLICATION

The CJC™ B 27/27 Filter Insert is used in CJC™ Filters ideal for filtration of mineral and synthetic based

- hydraulic oils
- gear oils
- lube oils
- turbine lube oils
- honing oils
- rolling oils

FILTRATION CAPABILITY

• Particle Removal

All CJC™ Filter Inserts have the following filtration degree:

- **3 µm absolute:**
98.7% of all solid particles > 3 µm
- **0.8 µm nominal:**
50% of all solid particles > 0.8 µm

are retained in each pass.

The dirt holding capacity of an B 27/27 Insert is **4 litres** of evenly distributed solids.

• Degradation Products

Oxidation by-products, resin / sludge, and varnish are retained by the cellulose material. The cellulose will retain **appr. 4 kg** of degradation products.

• Water Removal

The water absorption potential is up to 50% (i.e. **2000 mL H₂O**) of the total contaminant holding capacity.

DIMENSIONS

The figures below are nominal:

Diameter: 27 cm
Height: 27 cm

COMPONENT

CJC™ Filter Inserts type B consist of bonded discs. Ingredients: Wood cellulose and cotton linters.

IDENTIFICATION

To order the B 27/27 Filter Insert, please use:

Article No:
1 x 27/27: PA5601301
2 x 27/27: PA5601304



CJC™ B 27/27 Filter Insert